

CMX-MTP24SMST Datasheet

The Camplex CMX-MTP24SMST breakout series features MTP24 APC male connectors that break out into 24 Standard ST/UPC male Single Mode simplex fiber connectors. The MTP24 APC connectors ensure low insertion loss and high performance for permanent installations.

The CMX-MTP24 breakout series are ideal for breaking out your Single Mode and Multimode MTP/MPO 24 fiber breakouts into ST, LC, and other industry-standard connectors. They are perfect for breakouts, patch panels, rack-to-rack, or rack-to-equipment installations in the studio or field deployment.

Features:

- Male APC Single Mode MTP24 connector breaks out to (24) Simplex ST/UPC Single Mode connectors
- Low insertion loss and high return loss
- Meets TIA/EIA-568C.3 and GR-326-CORE Requirements
- UL Plenum (OFNP/FT6) rated

Specifications:

- **Cable Type:** SM 24 Fiber 9/125 μ m (Single Mode)
- **Cable O.D.:** 0.11in (3mm)
- **Simplex Leg O.D.:** 0.07in (2mm)
- **ST/UPC Simplex Connector Furcation:** 0.07in (2mm)
- **Connector A:** MTP/APC 24 Fiber Male Single Mode
- **Connector B:** ST/UPC Single Mode Simplex
- **Insertion Loss (MTP):** <0.35dB
- **Insertion Loss (ST):** <0.3dB
- **Return Loss (MTP):** >60dB
- **Return Loss (ST):** >50dB
- **Max Attenuation:** 0.34/0.20dB/km (1310/1550nm)
- **Min Bend Radius Fixed:** 2.3in (6cm)
- **Min Bend Radius Flexing:** 1.18in (3cm)
- **Operating Temperature:** -4°F to 158°F (-20°C TO +70°C)
- **Storage Temperature:** -40°F to 158°F (-40°C TO +70°C)

