

OPADAP Series

The OPADAP Series are breakout adapters, that allows you to connect your Neutrik opticalCON DUO/QUAD and MTP cables to standard Single Mode or Multimode LC, SC, ST, UPC or APC fiber optic connectors.

Cables are fully tested to ensure reliable performance in critical applications and are available in Single Mode, or Multimode, SC, LC, ST, UPC and APC configurations.

Features:

- Rugged and lightweight
- Rubber Dust caps for additional protection
- Low Insertion loss and Low Return loss
- IP65 protection in mated condition with SCDP
- Made in the USA by a Certified opticalCON assembler

Specifications:

- **Cable O.D:** 0.07in (2.0mm)
- **Insertion Loss:** ≤ 0.3 dB
- **Return Loss:**
 - Multimode UPC ≥ 35 dB
 - Single Mode UPC ≥ 50 dB
 - Single Mode APC ≥ 60 dB
- **Min Bending Radius:**
 - Static: 1.26in (32mm)
 - Dynamic: 1.4in (35.56mm)
- **Operating Temperature:** -4°F to 158°F (-20°C to +70°C)
- **Storage Temperature:** -40°F to 158°F (-40°C to +70°C)



*Available in Single Mode, or Multimode, SC, LC, ST, UPC and APC configurations.

Multimode Adapters

Multimode DUO					
Part Number	UPC	APC	LC	SC	ST
OPADAP-1	X		X		
OPADAP-5	X			X	
OPADAP-14	X			X	
Multimode QUAD					
Part Number	UPC	APC	LC	SC	ST
OPADAP-3	X		X		
OPADAP-7	X				X
OPADAP-16	X			X	

Single Mode Adapters

Single Mode DUO					
Part Number	UPC	APC	LC	SC	ST
OPADAP-2	X		X		
OPADAP-6	X				X
OPADAP-9		X	X		
OPADAP-10		X		X	
OPADAP-13	X			X	
OPADAP-17	X		X		
OPADAP-18		X		X	
Single Mode QUAD					
Part Number	UPC	APC	LC	SC	ST
OPADAP-4	X		X		
OPADAP-8	X				X
OPADAP-11		X	X		
OPADAP-12		X		X	
OPADAP-15	X			X	